

<b>Product Description</b>	Perma-Patch Regular Mix 60 lb. Bag
<b>MFG Number</b>	PP-60-C
<b>Packaging</b>	4-ply, poly-lined, water-resistant kraft paper bag.
<b>Storage</b>	Bags should be kept in a dry/covered area.
<b>Also Available</b>	PP-40-PLC, PP-50-PLC: 40 and 50 lb. Poly-Woven Bags PP-30-CP, PP-30-FP, PP-50-CP, PP-50-FP: 30 and 50 lb. Pails
<b>Usage</b>	<ul style="list-style-type: none"> <li>Use for quick and permanent repairs of potholes, depressions, utility cuts, cable/fiber optic trenches, around manhole covers, utility boxes, and bridge expansion joints.</li> <li>Apply in any weather condition in temperatures ranging from -5° to 105° F without any mixing, tack coating, or costly waiting time.</li> </ul>
<b>Performance</b>	Perma-Patch was independently rated the #1 permanent cold-applied patch repair material by the Federal government in their Strategic Highway Research Program (SHRP) study with the lowest failure rate. All other tested products had failure rates 30%–70% higher. Please see the SHRP report on our website at <a href="http://permapatch.com/shrp">permapatch.com/shrp</a> .
<b>Material Type</b>	Polymer-Modified Permanent Repair Patch for Road Repair and Utility Restorations
<b>Aggregate</b>	Precisely Graded ¼" & Smaller Virgin Aggregate
<b>Binder</b>	<ul style="list-style-type: none"> <li>Proprietary Polymer Modified Blend for High Strength and Easy Pouring in all conditions</li> <li>Binder enables long-term sealing and self-healing properties.</li> <li>Ideal for the most difficult applications including bridge joints, transition areas, and areas of multiple materials such as transitions including asphalt, concrete, and metal.</li> </ul>
<b>Activation</b>	Pressure-activated. Hardens by compaction. After compaction, the repair area is ready for immediate traffic.
<b>Bonds to</b>	Asphalt, Concrete, Steel, & Wood. It does not stick to rubber tires.
<b>Road Surfaces</b>	Asphalt & Concrete
<b>Packaging</b>	60 lb. Easy-Open Easy-Pour bags, 50 bags per pallet
<b>Origin</b>	Manufactured in USA
<b>Application Thickness</b>	<ul style="list-style-type: none"> <li>Minimum: ¼"</li> <li>Maximum depth: No Maximum. Apply in 3" lifts.</li> </ul>
<b>How to Use   Preparation</b>	<ul style="list-style-type: none"> <li>Perma-Patch is ready to use and can be poured from the bag. No mixing, no tack coat, and no special preparation are necessary.</li> <li>Tips for Success: Remove any large/loose aggregate, pour product in (overfill by ½"–¾"), spread out evenly with rake or shovel, and compact using a hand tamper, vibrating plate compactor, or the pressure of passing traffic.</li> </ul>
<b>Coverage</b>	Each 60 lb bag fills 0.48 cubic feet of area—6 sq ft area, 1" deep.
<b>Shelf Life</b>	Guaranteed 2 Years
<b>Inventory</b>	Every bag stamped with lot number and best used by date (2 years). Helps your team make sure they use material in a timely fashion.
<b>Accepts Traffic</b>	Immediately.
<b>Color</b>	Black



# PP-60-C Spec Sheet